

- Powerful 3/8 HP Motor with Variable Frequency Drive
- Belt Widths: 4" (10.16 cm) min. to 36" (91.44 cm) max. in 2" (5.08 cm) increments
- Conveyor Lengths: 2' (60.96 cm) min. to 12' (365.76 cm) max.
- Max. Conveyor Load Capacity: Up to 150 Lbs. (56 kg)
- Standard Emergency Stop
- Available in a Wide Variety of Belt Materials
- Standard Clear Anodized Extruded Aluminum Side Plates
- Standard Locking Casters and Leveling Feet
- Standard Adjustable Guide Rails
- Standard Stainless Steel Frame and Applicator Supports







Continuous Belt Conveyor

Accessories

Our rugged new continuous friction belt conveyor line is designed to add versatility to your Label-Aire applicator while fitting perfectly into your existing production line. The Label-Aire Continuous Belt Conveyor features a powerful yet efficient 3/8 HP motor that can move

label-aire®

your product at speeds up to 125 feet (38.1 m) per minute. Belt widths range from 4" (10.16 cm) to 36" (91.44 cm) max. with conveyor lengths from 2 feet (60.96 cm) to 12 feet (365.76 cm). Like all Label-Aire products, our Continuous Belt Conveyor is built to meticulous quality standards and designed to withstand the most demanding operation.



Distributed by: