Sleeve







Sleeve Applicator Series 8300

Labeling System

Model

# Sleeve Applicator Series 8300 Specifications


The NEW Label-Aire® Sleeve Applicator Series Model 8300 is a fast, efficient, and easy-to-operate single head shrink sleeve labeling system that can easily handle most tamper-evident, overall-, middle-, and full-body sleeve (including sustainable film) applications.

Specifically designed for high speed runs of up to 200 products per minute, the new Model 8300 will easily handle all industry standard sleeve materials and a wide range of container shapes and sizes.

The Label-Aire Sleeve Applicator Series Model 8300 is designed to meticulous specifications including: Easy-to-operate PLC controls, stainless steel/anodized aluminum construction, high-speed operation, and stepper drive technology.

Sleeve Applicator Series 8300 Advanced Features		
HMI touch screen	User-friendly controls for reduced set up time.	
Stainless steel and anodized aluminum construction	Handles the most hostile work environments.	
Patented cutting assembly	Results in high productivity and long blade life.	
Stepper drive technology	Advanced film feed system ensures accuracy.	
Transparent safety doors and covers	Provides full operator protection during labeling.	
Wide product capability	Handles product widths from 1.0625" (26.9875 mm) to 4.625" (117.475 mm) for added versatility.	
Variety of applications	Tamper evident, overall-body, middle-body, and full-body sleeve.	





Stated dimensions are approximations. Please consult factory if dimensions are required for line integration.

## Dimensions:

Height: 101.57" (2,580 mm) Length: 111.81" (2,840 mm) Width: 33.46" (850 mm)

#### Weight:

Approx. 1,875 lbs. (700 kg)

## **Maximum Sleeve Lay Flat:**

7.48" (190 mm)

#### **Maximum Product Width:**

1.0625" (26.9875 mm) to 4.625" (117.475 mm)

# **Product Throughput Rate:**

Up to 200 ppm

#### **Electrical:**

220 Volts AC 50/60 Hz 5 Amps. (10 kw), Three phase

# Options:

Consult factory for shrink tunnel and additional options.